

REPEL DRY

A CHEMICAL CRYSTALLINE WATER REPELLENT TREATMENT FOR DRY CEMENTITIOUS SURFACES

SINCE 1992

SABS Tested

Prevents water and moisture ingress that leads to paint and cement failures.

Water or moisture ingress is restricted in positive and negative manner.

Acide & Alkali resistant

Does not alter the appearance

Inorganic crystal forming

Bricks

Slasto

Paving

Sandstone

Plaster surfaces

Cement roof tiles

Prefabricated walls

New & aged plaster surfaces

Please contact us for further information.

The information given in this Technical Data Bulletin is based upon laboratory research, as well as extensive field work and application.

This information is based on AquaGO®'s present state of knowledge and is intended to provide general information on AquaGO®'s products and their methods of use.

The prospective user is recommended to determine the suitability of AquaGO®'s suggestions and products before adopting them on a commercial scale.

DESCRIPTION

AquaGO® DRY is a chemical procedure for the treatment of cementitious surfaces that are devoid of free water or moisture.

Based on innovative proprietary CSC 45/10 hydrophobic technology.

After full cure water or moisture is permanently repelled and in water or moisture ingress is unable to take place.

SURFACE PREPARATION

Remove all dust, dirt or foreign debris.

Ensure that the surface is 100% dry.

SAFETY

- Do not apply in confined areas.
- Do not dispose of in drains or sewers.
- Do not puncture containers.
- In the event of spillage, cover entire area with fine sawdust.
- Use PPE at all times.
- Do not breath mist.
- Wear surgical gloves during application.
- Do not apply when rainfall is eminent.
- Do not apply during strong wind.
- Avoid overspray on surrounding equipment, flowers and vehicles.
- Do not smoke during application.
- Do not consume food during application.

EYES:

Wash with copious amounts of potable water.

CONSUMPTION:

Do not induce vomiting. seek medical care.

HANDS:

Wash thoroughly with a mild soap solution. Apply barrier cream.

APPLICATION

Spray apply by means of household pesticide applicator or Agri back pack for large surfaces.

Ensure saturation and avoid damming.

Remove excess liquid immediately with a moist cloth.

Protect ferrous metals and glazing from overspray.

Always commence application from the top.

TECHNICAL DATA

COLOUR	Pinkish transparent
SOLVENT	Water based
SG	0.98
PH	12-14
TESTING	Water ingress Wacker Academy test method
RESULT	0% After 72 hours
TEMP	28°C maximum 8°C minimum
SPR	4-6 m ² /litre



Contractors Supply Company

Manufactured and distributed by CSC Builders Mart (Pty) Ltd
t/a Contractors Supply Company
Affiliated with PCT Water Repellent Technology cc

Contact Suzette - Sales manager

☎ 076 059 5142, ✉ suzette@contractorsupply.co.za